

High Intensity Discharge Lamps

Model	Wattage (W)	Volts (V)	Cap	Product Description	GE Product Code	TU Product Code	Lumen (lm)	CCT (K)	CRI (Ra)	Operating position	Rated Life (h)	Length (mm)	Diameter (mm)	Energy Consumption (kWh)	EEC	Pack Qty
Lucalox™ Standard Tubular Clear																
2	70	90	E27	LU 70/90/MO/T/E27	46221	93102205	6 100	2000	25	U	28 000	156	39	78	A+	25
1	100	100	E40	LU100/100/MO/T/40	93767	93102242	9 600	2000	25	U	28 000	211	48	107.6	A+	12
1	150**	100	E40	LU150/100/40	44244	93102199	15 300	2000	25	U	28 000	211	48	163.8	A+	12
1	250**	100	E40	LU250/T/40	22453	93102171	28 500	2000	25	U	28 000	260	48	276.8	A+	12
1	400**	100	E40	LU400/T/40	11678	93102162	48 000	2000	25	U	28 000	278	48	431.9	A+	12
1	1000	250	E40	LU1000/40	85886	93102216	130 000	2100	22	U	24 000	383	79	1100	A+	6
1	1000	110	E40	LU1000/110/T/40	45751	93102202	130 000	2000	25	U	24 000	374	68	1067.1	A++	4
2	73	90	E27	LU70/90/HO/T/E27 MIC	93031989	93102250	6 500	2000	21	U	28 000	156	39	80.6	A+	25
1	100	100	E40	LU100/100/HO/T/E40 MIC	93032129	93102252	10 400	2000	21	U	28 000	211	48	110.44	A+	12
1	150	100	E40	LU150/100/HO/T/E40	97241	93102249	17 500	2000	21	U	28 000	283	48	172.7	A+	12
1	250	100	E40	LU250/100/HO/T/E40 MIC	93032128	93102251	32 500	2000	21	U	28 000	260	48	291.93	A+	12
2	400	100	E40	LU400/HO/T/E40	97240	93102248	56 200	2000	21	U	28 000	260	48	444.4	A++	12
Lucalox™ Standard Elliptical Diffuse																
3	70	90	E27	LU70/90/MO/D/E27	46217	93104669	5 750	2000	25	U	28 000	156	72	77.8	A	12
Lucalox™ Internal Ignitor Elliptical Clear																
3	70	90	E27	LU 70/90/MO/I/E27	46209	93102204	6 100	2000	25	U	17 500	156	72	79.4	A+	12
Lucalox™ Internal Ignitor Elliptical Diffuse																
4	70	90	E27	LU70/90/MO/D/I/E27	46186	93102203	5 750	2000	25	U	17 500	156	72	78.2	A	12
Mixed Light																
6	160	230-240	E27	OT ML 230-240V 160W E27 GE 1/24 MIC DS**	63675	93104681	3 100	4200	52	VBU±30	8 000	170	76	185.4	D	24
5	250	230-240	E40	OT ML 230-240V 250W E40 GE 1/12 MIC DS**	63678	93104684	5 500	3800	52	U	8 000	227	91	277.5	C	12
6	250	230-240	E27	OT ML 230-240V 250W E27 GE 1/12 MIC DS**	63677	93104683	5 500	3800	52	U	8 000	227	91	277.5	C	12
5	500	230-240	E40	OT ML 230-240V 500W E40 GE 1/10 MIC DS**	63676	93104682	14 000	3800	45	U	8 000	292	121	545.4	B	10

**Not CE compliant product

